

Electrolux Professional



Electrolux

# Range Overview

Commercial  
Laundry



*Thinking of you*  
**Electrolux**

# Excellent solutions that meets your needs

*Commercial laundries need to be competitive. That is why our solutions are developed to deliver significant time and money savings in the total process through 'Excellence inside' – intelligent features and unique extras.*

## Electrolux Excellence



Excellence is central to everything we do. By anticipating our customers' needs, we strive for Excellence with our people, innovations, solutions and services. Thus making our customers' work and life easier and more profitable.

## Washer Extractor Control

ensures the best utility cost optimisation and customising



### Clarus Control®

- ▶ Fully programmable with up to 194 programs for unparalleled versatility
- ▶ Create new programs directly on Clarus Control® panel or on your PC with Laundry Program Manager, then transfer them to machines via memory card
- ▶ Intelligent parameters save time, energy and water while delivering excellent wash and rinse results in every application
- ▶ 8 liquid detergent signals, plus efficient detergent dosing via connection to Efficient Dosing System
- ▶ Process monitoring via Certus Management™ Information System



### Compass Control®

- ▶ Up to 50 wash programs, including 10 programmable for optimum flexibility
- ▶ Create custom Compass Control® wash programs on your PC with Laundry Program Manager, then transfer them to machines via memory card
- ▶ 5 liquid detergent signals for automatic dosing: saves money and prevents overdosing thanks to the Efficient Dosing System
- ▶ Automatic Saving System: save up to 50% on water for half loads
- ▶ Available in 13 languages

## Tumble Dryer Control

ensures the best flexibility and usability



### Compass Pro®

- ▶ Flexible and customisable
- ▶ Up to 55 programs available (15 own made)
- ▶ Large, clear display in 18 languages, plus integrated timer
- ▶ Process monitoring via Certus Management™ Information System



### Unique Triangle Technology

The best flexibility and process performance

- ▶ **Economy:** optimum cost-effectiveness due to low energy consumption
- ▶ **Time:** the highest output due to short process times
- ▶ **Care:** the best drying results



### Selecta Control®

- ▶ Accurate temperature/humidity control for quick, efficient drying
- ▶ Automatic inversion of drum rotation
- ▶ Automatic cooling cycle reduces creasing and improves finish
- ▶ 9 programs, including for entire electronic cycle, exact temperature control and constantly high drying performance
- ▶ Select drying time, cooling and reverse action
- ▶ Continuous self-testing, displays and logs error codes for easy troubleshooting
- ▶ Process monitoring via Certus Management™ Information System

## Ironer Control

ensures the best results thanks to process optimisation



### Electronic control

- ▶ Large, intuitive display
- ▶ Indicator light informs operator if retained humidity after ironing is too high
- ▶ Ensures optimum dryness and hygiene, plus compliance with risk analysis and bio-contamination quality control
- ▶ Process monitoring via Certus Management™ Information System



### Electro-mechanical control

- ▶ Easy to read and set
- ▶ Ironing temperature and speed can be adjusted at any time
- ▶ Autostop function to maximise ironing belt lifetime (standard)

# Washer Extractors

Choose the solution that suits you best

● standard ○ option  
x available – not available



Washer Extractors H High Spin Range	W4130H	W4180H	W4240H	W4300H	W4400H	W4600H	W4850H	W41100H
Drum volume, l	130	180	240	300	400	600	850	1100
Dry weight capacity, kg/lb	14/30	20/45	27/60	33/75	45/100	65/145	90/200	120/265
Extraction, rpm	980	930	890	820	825	800	720	663
G-factor	350	350	350	300	350	350	350	300
Water consumption cold/hot, l*	86/22	124/31	167/42	202/52	programmable	programmable	programmable	programmable
Width, mm	910	970	1020	1020	1330	1390	1640	1640
Depth, mm	785	870	915	1060	1360	1600	1630	1845
Height, mm	1325	1410	1440	1445	1890	2015	2230	2230
Width, in	35 13/16"	38 3/16"	44 2/16"	44 2/16"	52 6/16"	54 12/16"	64 9/16"	64 9/16"
Depth, in	30 14/16"	34 4/16"	36	65 6/16"	53 9/16"	63	64 3/16"	72 10/16"
Height, in	52 3/16"	55 8/16"	56 11/16"	56 14/16"	74 7/16"	79 5/16"	87 13/16"	87 13/16"
Electric/Steam/Non-heated	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	-/x/x	-/x/x
Compass Control®	●	●	●	●	–	–	–	–
Clarus Control®	○	○	○	○	●	●	●	●
Wet-cleaning Excellence	○	○	○	○	○	○	○	○

\* Consumption data: Normal 60 °C (140 °F) program  
(without pre-wash, 3 rinses at rated capacity electrical heating)



Side load Barrier Washers Side load Washer Extractors	WB4130H	WB4180H	WSB4250H WS4250H	WSB4350H WS4350H	WSB4500H WS4500H	WSB4650H WS4650H	WSB4700H WS4700H	WSB4900H WS4900H	WSB41100H WS41100H
Drum volume, l	130	180	250	350	500	650	700	900	1100
Dry weight capacity, kg/lb	13/29	18/40	25/55	35/77	50/110	65/143	70/154	90/198	110/242
Extraction, rpm	910	910	910	910	910	910	720	720	720
G-factor	300	300	350	350	350	350	300	300	300
Width, mm	910	970	1045	1285	1567	2000	1496	1726	1956
Depth, mm	875	975	1055	1055	1055	1055	1483	1483	1483
Height, mm	1325	1410	1610	1610	1610	1610	2040	2040	2040
Width, in	35 13/16"	38 3/16"	41 2/16"	50 9/16"	61 11/16"	78 12/16"	58 14/16"	67 15/16"	77
Depth, in	30 14/16"	38 3/32"	41 9/16"	41 9/16"	41 9/16"	41 9/16"	58 6/16"	58 6/16"	58 6/16"
Height, in	52 3/16"	55 1/2"	63 6/16"	63 6/2"	63 6/16"	63 6/2"	80 5/16"	80 5/2"	80 5/16"
Electric/Steam/Gas/Thermal Oil	x/x/-/-	x/x/-/-	x/x/x/x	x/x/x/x	x/x/x/x	x/x/x/x	x/x/-/x	x/x/-/x	x/x/-/x
Compass Control®	●	●	–	–	–	–	–	–	–
Clarus Control®	○	○	●	●	●	●	●	●	●
Wet-cleaning Excellence	○	○	○	○	○	–	–	–	–

● standard ○ option  
x available – not available



**Washer Extractors**  
X Extra Spin Range

W4280X W4350X W4600X

Drum volume, l	280	350	600
Dry weight capacity, kg/lb	28/62	35/77	60/135
Extraction, rpm	805	650	630
G-factor	300	300	300
Water consumption cold/hot, l*	312/0	320/67	598/105
Width, mm	935	1085	1145
Depth, mm	970	1105	1375
Height, mm	1455	1570	1670
Width, in	36 13/16"	42 11/16"	45 1/16"
Depth, in	38 3/16"	43 8/16"	54 2/16"
Height, in	56 14/16"	61 13/16"	65 12/16"
Electric/Steam/Non-heated	-/x/x	x/x/x	x/x/x
Compass Control®	●	●	–
Clarus Control®	○	○	●

\* Consumption data: Normal 60 °C (140 °F) program  
(without pre-wash, 3 rinses at rated capacity electrical heating)



**Wash&Dry**

WD4130 WD4240

Drum volume, l	130	240
Dry weight capacity, kg/lb	14/30	27/55
Extraction, rpm	980	980
G-factor	350	350
Water consumption cold/hot, l*	48/12	82/22
Electric/Electric	●	●
Width, mm	910	1020
Depth, mm	1110	1350
Height, mm	1330	1450
Width, in	35 13/16"	44 2/16"
Depth, in	43 8/16"	53 5/32"
Height, in	52 3/16"	57 1/16"
Electric/gas	○	○
Non heated/gas or electric	○	○
Compass Control®	●	●
Wet-cleaning Excellence	–	○

\* Consumption data: Normal 60 °C (140 °F) program

## Tumble Dryers

Find the solution that meets your needs



**Tumble Dryers**

T4250 T5290 T4300LE T4350 T5550 T5675 T4900 T41200

Drum volume, l	250	290	300	350	550	675	900	1200
Dry weight capacity, kg/lb, Filling factor 1:18	13,9/30	16,1/35,5	13,6/30	19,4/42	30,5/67,2	37,5/82,7	50/110	66,7/147
Width, mm	790	710	790	790	960	960	1290	1290
Depth, mm	900	1155	1284	1120	1315	1510	1295	1485
Height, mm	1720	1675	1663	1720	1855	1855	2455	2455
Width, in	31 1/8"	27 15/16"	31 1/8"	31 1/8"	37 13/16"	37 13/16"	50 13/16"	50 13/16"
Depth, in	35 7/16"	45 1/2"	50 9/16"	44 1/8"	51 3/4"	59 7/16"	51	58 7/16"
Height, in	67 11/16"	65 15/16"	65 1/2"	67 11/16"	73 7/16"	73 1/16"	97	97
Sliding door	–	–	–	–	–	–	○	○
Electric/Gas/Steam	x/x/x	x/x/x	●/–/–	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x
Selecta Control®	●	–	●	●	–	–	●	●
Compass Control®	–	–	–	–	–	–	–	–
Compass Pro®	–	●	–	–	●	●	–	–
Residual Moisture Control	○	○	●	○	○	○	●	●
Reversing Drum Action	○	○	●	○	○	○	●	●
Wet-cleaning Excellence	○	○	–	○	○	○	○	○

# Ironers


Discover which solution is best for you

● standard ○ option  
x available – not available



Ironers	IC43316	IC43320	IC44819	IC44821	IC44825	IC44828	IC44832	IC44819 FFS	IC44825 FFS	IC44832 FFS
Roll diameter mm/in	325/13	325/13	479/19	479/19	479/19	479/19	479/19	479/19	479/19	479/19
Ironing width mm/in	1650/65	2065/81	1910/75	2120/83	2540/100	2750/108	3170/125	1910/75	2540/100	3170/125
Width, mm	2030	2445	2575	2785	3205	3415	3835	3810	4410	4910
Depth, mm	690	690	1070	1070	1070	1070	1070	1730	1730	1730
Height, mm	1145	1145	1270	1270	1270	1270	1270	1675	1675	1675
Width, in	79 15/16"	27 15/16"	26 12/16"	126 3/16"	126 3/16"	134 7/16"	151	150	173 10/16"	193 5/16"
Depth, in	27 3/16"	45 1/2"	40 6/16"	40 6/16"	40 6/16"	40 6/16"	40 6/16"	68 2/16"	68 15/16"	68 15/16"
Height, in	45 1/16"	65 15/16"	50	50	50	50	50	65 15/16"	65 15/16"	65 15/16"
Width, mm (with Feeding and Length Folding)	–	–	2575	2785	3205	3415	3835	–	–	–
Depth, mm (with Feeding and Length Folding)	–	–	1280	1280	1280	1280	1280	–	–	–
Height, mm (with Feeding and Length Folding)	–	–	1460	1460	1460	1460	1460	–	–	–
Width, in (with Feeding and Length Folding)	–	–	101 16/16"	126 3/16"	126 3/16"	134 7/16"	151	–	–	–
Depth, in (with Feeding and Length Folding)	–	–	50	50	50	50	50	–	–	–
Height, in (with Feeding and Length Folding)	–	–	57	57	57	57	57	–	–	–
Electric/Gas/Steam	x/-/x	x/-/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x	x/x/x
Evaporation capacity l/h	19.5	24.5	38/57/35	40/63/37	48/75/46	51/81/51	59/93/59	38/57/35	48/75/46	59/93/59
Speed m/minute	0.5 to 5.5	0.5 to 5.5	1.5 to 9	1.5 to 9	1.5 to 9	1.5 to 9	1.5 to 9	1.5 to 11	1.5 to 11	1.5 to 11
Ironer Moisture	○	○	●	●	●	●	●	●	●	●
Dubblum™	–	–	○	○	○	○	○	●	●	●
Automatic feeding	–	–	○	○	○	○	○	●	●	●
Automatic folding	–	–	○	○	○	○	○	●	●	●

\* For electric and gas heated versions



Ironers	C-Flex 900	C-Flex 1200
Roll diameter mm/in	900/35	1200/47
Ironing width mm/in	2700 to 4200/118 to 165	2700 to 4200/118 to 165
WidthxDepthxHeight (1 roll), mm*	4500x1685x1560	4500x1985x1760
WidthxDepthxHeight (2 rolls), mm*	4500x2955x1560	4500x3555x1760
WidthxDepthxHeight (3 rolls), mm*	4500x4225x1560	4500x5125x1760
WidthxDepthxHeight (1 roll), in	165 6/16" x 78 9/16" x 61 7/16"	165 6/16" x 91 5/16" x 69 5/16"
WidthxDepthxHeight (2 rolls), in	165 6/16" x 130 14/16" x 61 7/16"	165 6/16" x 157 5/16" x 69 5/16"
WidthxDepthxHeight (3 rolls), in	165 6/16" x 183 11/16" x 61 7/16"	165 6/16" x 219 2/16" x 69 5/16"
Steam/Gas/Thermal Oil	x/x/x	x/x/x
Evaporation capacity l/h	189 to 731	230 to 1260
Number of rolls	1 to 3	1 to 3
Speed m/minute	5 to 50	5 to 50

\* For 3.3 m working width models

## Other Equipment

● standard   ○ option  
x available   – not available

Drying Cabinets	FC48	TS5121
Garments/hours*	70	
Loading Capacity kg/lb		6-8/12-18
Width, mm	870	1200
Depth, mm	1300	580
Height, mm	1975	1820
Width, in	34 1/4"	47 1/4"
Depth, in	51 3/16"	22 13/16"
Height, in	77 3/4"	71 5/8"
Electric/Gas/Steam	x/x/x	●/-/-
Microprocessor	semi-programmable	pre-fixed programmes

\* Estimated production power

A wide range of options and accessories (trolleys, bases, condensing units, etc) is also available, ask our local offices!



FSU1 spotting table



FSF2 shirt finisher



FSF3 shirt finisher



FFT-S form finisher



FPA6-WC collar and cuff press



FFT-D form finisher



FTT1 trouser topper



FPA3-D leg shape press



FIT2WC ironing table

## Unique Service Excellence

Always near.  
Always there for you

A reliable, global presence: Electrolux Professional offers the most extensive service network of skilled, authorized partners for daily tasks: installation, spare parts and maintenance. All of them provide an efficient customer service and fast technical assistance. A global service network for prompt, expert advice worldwide.

- ▶ 1,900 authorised service centres
- ▶ Over 7,000 expert technicians
- ▶ 44,000 available spare parts in stock
- ▶ Spare parts are guaranteed for at least 10 years from the end of production
- ▶ 24-48 hr spare parts delivery worldwide



Thinking of you  
**Electrolux**

전체화면을 종료하려면

Esc

을(를) 누르세요.

### Commercial Laundry Solutions

Hygiene Laundry Solutions

In-House Laundry Solutions

Consumer-Operated Laundry Solutions



## Excellence with the environment in mind

Electrolux Professional solutions perfectly match the customers' needs, including the areas of reliability, cost efficiency and sustainability. The products are the best in terms of quality – durability with low running costs. Some installations have been running for more than 40 years!

- ▶ All Electrolux factories are ISO 14001-certified
- ▶ All Electrolux Professional products are designed for low water, energy and detergent consumption, and for low emissions into the environment
- ▶ All Electrolux Professional products are ROHS-compliant and over 95 % recyclable
- ▶ All units are quality tested, piece by piece, and all of the functions are singularly checked by expert technicians
- ▶ In the last five years, more than 70% of Electrolux Professional solutions have been updated with features that are always designed with the needs of customers and environmental considerations in mind



Discover the Electrolux Excellence  
and share more of our thinking at  
[www.electrolux.com/laundrysystems](http://www.electrolux.com/laundrysystems)