

20-80 lb. VENDED WASHERS

QUALITY, VALUE, DURABILITY = FIVE CAPACITIES = EASY-TO-USE CONTROLS



45 lb. capacity model MCT18E4

MILNOR cabinet-style washers are cost-effective for busy stores, and built for high profits and long life.

These washers are designed by Milnor to deliver high profits, simple operation, and the same legendary durability you would expect from their other machines.

Wash big loads quickly

These frontloaders help customers wash quickly. A 20-25 lb. washer has a cylinder volume of 3.37 cu. ft.. The 35 lb. model features a 4.3 cu. ft. basket and the 45 lb. machine has a cylinder volume of 6.4 cu. ft. The 60 lb. washer has a 9.0 cu. ft. basket and the 80 lb. washer has a 12.37 cu. ft. cylinder volume for bulky or large loads. Multi-compartment wash supply dispenser for liquid or powder chemicals is standard.

Easy-to-use controls



Simple, easy-to-follow directions are printed in English and Spanish. A bright display counts down as coins are deposited. The display also counts down the number of minutes left in the total cycle, as well as the microprocessor's function (such as "add fabric softener" or "rinse") occurring at that moment. The microprocessor identifies certain error codes,

which may be corrected by attendant (saving downtime). The formula load count accumulator provides a running count for each of the seven formulas, allowing greater reporting to the store owner/manager. Milnor's microprocessor control delivers two sets of seven wash formulas, each with programmable vend prices. The first set features standard formulas ranging from a Quick Wash to a Heavy Soil option. The second set of seven formulas uses Milnor's GreenTurn™ programming decisions, featuring fewer rinses, less hot water use and faster processing times. Either formula set can be selected by the store owner.

Superior washing quality

A reversing washing action means cleaner washing with no tangling or knotting. This is the same lift-and-drop action that won Milnor its reputation for superior washing quality among commercial hundre or superior.

laundry operators. The proven single-motor inverter drive delivers a wash speed (reversing), load distribution speed (to minimize vibration during high-speed extraction), and final extraction.

Choose from 5 sizes

Select the model that best meets your requirements and budget. The popular 20-25 lb. model is an excellent machine for any coin store. The 35 lb. washer is a great replacement machine for most competitive 30 and 40 lb. machines in the field. The 45 lb, 60 lb. and 80 lb. models are ideal for the larger part of your equipment mix.

Suds overflow protection

An overflow pipe at the rear of the machine sends excess water and suds to the drain, helping keep floors dry. This reduces the danger of slipping (beneficial for unattended stores).

Easy-access gravity drain

There's no troublesome pump. Milnor's simple gravity valve is frontmounted, drains quickly, and avoids clogging.

Rugged vault deters theft

Ideal for unattended areas. Made of heavy gauge steel, the optional vault holds about \$100 in quarters. All wash formulas have different vend prices and are completely programmable.



Pellerin Milnor Corporation P.O. Box 400, Kenner, LA 70063 USA Phone: (504) 712-7656 Toll Free: (800) 469-8780 www.milnorcoin.com milnorinfo@milnor.com



35 lb. capacity model MCT16E5

WASHER-EXTRACTOR SPECIFICATIONS

	MCR12E5	MCT16E5	MCT18E4	MCT27E4	MCR36E4
Capacity - Ib (kg)	20-25 (9-11)	35 (16)	45 (20)	60 (27)	80 (36)
Cylinder diameter x depth - in (mm)	23 x I4 (584 x 356)	23 x 18 (584 x 457)	28 x 18 (711 x 457)	30 x 22 (762 x 559)	36 x 21 (914 x 533
Gross cylinder volume - cu. ft. (L)	3.37 (95)	4.3 (121)	6.4 (180)	9.0 (255)	12.37 (350)
Motor - HP	I.	1.5	3	4	5.5
Wash speed - RPM	43	43	39	38	37
Distribution speed - RPM	90	90	71	65	70
Extract - RPM	530	530	480	485	442
Extract G forces	90	90	90	100	100
Drain valve - in (mm)	2 (51)	2 (51)	3 (76)	3 (76)	3 (76)
Inlet valve - in (mm)	0.75 (19)	0.75 (19)	0.75 (19)	0.75 (19)	0.75 (19)
Width - in (mm)	26 (660)	29 (737)	34.45 (875)	34.45 (875)	40.29 (1023)
Depth - in (mm)	35 (889)	42.13 (1070)	47.41 (1204)	51.75 (1314)	52.13 (1324)
Height - in (mm)	43 (1092)	43.2 (1097)	52.70 (1339)	56.25 (1429)	60.81 (1545)
Approx net weight - Ib (kg)	494 (224)	595 (270)	826 (375)	1156 (525)	1442 (640)

* Depending on density and soil content of goods

** Approximate

*** With standard accessories

Specifications and appearance subject to change without notice. Contact factory for acoustics data.